



# NEMO EVALUATIONS REPORT

Report No.: NER-FTS-002.B.R3  
Revision 3: 2025-06-25  
Page 1 of 7

FT Synthetics, Inc.  
FL46754-R3

**Nemo|cert.**  
353 Christian Street, Unit 12b  
Oxford, CT 06478  
(475) 888-CERT (2378)  
[www.nemocert.com](http://www.nemocert.com)

INSPECT

CERTIFY

EVALUATE

VALIDATE

QUALIFY

## NEMO EVALUATION REPORT (NER)



**FT Synthetics, Inc.**  
1 Campus Drive  
Parsippany, NJ 07054  
(973) 628-3000

**SUBJECT:** FT Platinum HT Roof Underlayments

**SCOPE:** This NEMO Evaluation Report (henceforth 'NER') is issued under F.A.C. [Rule 61G20-3](#) and the applicable rules and regulations governing Product Approval of construction materials in the State of Florida and ISO/IEC 17065 via [NEMO|cert.](#) NEMO Evaluations has evaluated the product described herein for compliance with the [Code sections noted herein](#).

**CODE:** 2023 Florida Building Code, 8<sup>th</sup> Edition  
2023 Florida Building Code, Residential, 8<sup>th</sup> Edition

**JURISDICTION:** Non-HVHZ and HVHZ

**NEMO CATEGORY:** Steep Slope

**FBC CATEGORY:** Roofing

**FBC SUB-CATEGORY:** Underlayment

**CSI DIVISION:** 07 00 00 Thermal and Moisture Protection  
07 30 05 Roofing Felt and Underlayment

**METHOD:** Method 1, Option C – Codified Material, Evaluation by Evaluation Entity

**COMPLIANCE STATEMENT:** **FT Platinum HT Roof Underlayments**, as produced by **FT Synthetics, Inc.**, have demonstrated compliance with the [Code sections noted herein](#) through testing in accordance with the referenced Standards, rational analysis and an ongoing quality assurance program. Compliance is subject to the [Installation Requirements](#) and [Limitations of Use](#) set forth herein.

**QUALITY ASSURANCE:** Evidence of current quality assurance shall be listing and labeling in accordance with the requirements of [NEMO|cert.](#)

**CONTINUED COMPLIANCE:** This NER is valid until such time the named product(s) change, the referenced Quality Assurance changes, or the evaluated Code provisions change. NEMO Evaluations require, at minimum, a complete review of this NER with each 3-year Code Cycle.

**BUILDING PERMIT REQUIREMENTS:** As required by the Building Official or Authority Having Jurisdiction to evaluate the installation of this product.

**ADVERTISEMENT:** "NEMO Evaluated" may be displayed in advertising literature. If any portion of the NER is displayed, it shall be displayed in its entirety.

**CERTIFICATION OF INDEPENDENCE:**

- ✓ NEMO CERT, LLC does not have, nor does it intend to acquire or will it acquire, a financial interest in any company manufacturing or distributing products it evaluates.
- ✓ NEMO CERT, LLC is not owned, operated or controlled by any company manufacturing or distributing products it evaluates.
- ✓ This is a building code evaluation. NEMO CERT, LLC is not, in any way, the Designer of Record for any project on which this NER, or previous versions thereof, is/was used for permitting or design guidance.





# NEMO EVALUATIONS REPORT

Report No.: NER-FTS-002.B.R3  
Revision 3: 2025-06-25  
Page 2 of 7

FT Synthetics, Inc.  
FL46754-R3



## 1. CODES, PROPERTIES AND STANDARDS:

CODE	SECTION	PROPERTY	STANDARD
2023 Florida Building Code, 8 <sup>th</sup> Edition	1504.2.1.4	Wind resistance	UL 1897
	1507.1.1, 1507.2.9.2, 1507.2.9.3, 1518.2, TAS 110	Material standard	ASTM D1970
	1507.3.3	Material standard	FRSA/TRI Manual
	1523.6.5.2.1, TAS 110	Material standard	TAS 103
	TAS 110	Accelerated Weathering	ASTM D4798
2023 Florida Building Code, Residential, 8 <sup>th</sup> Edition	R905.1.1, R905.2.8.2, R905.2.8.5	Material standard	ASTM D1970
	R905.3.3	Material standard	FRSA/TRI Manual

## 2. PRODUCTS:

TABLE 1: EVALUATED UNDERLAYMENTS (NEMO Certified. Consult <a href="#">Directory of Certified Products</a> for production location(s))		
PRODUCT	MATERIAL STANDARD	DESCRIPTION
FT Platinum HT-SA	ASTM D1970 <sup>1</sup>	Nominal 50-mil, self-adhering, multi-layered roof underlayment composed of a synthetic top facer bonded to a polymer modified bituminous layer and release film
FT Performance SA Leak Barrier		
FT Platinum HT-B	ASTM D1970 <sup>1</sup>	Self-adhered waterproofing membrane with butyl rubber adhesive and slip-resistant walking surface
FT Premier Butyl Leak Barrier		

## 3. INSTALLATION:

3.1 **FT Platinum HT Roof Underlayments** shall be installed in accordance with **FT Synthetics** published installation instructions, subject to the [Limitations of Use](#) noted herein. In case of conflict between published installation instructions and this NER, this NER governs.

3.1.1 The report holder's installation instructions shall be made available at the jobsite at all times during installation.

3.2 Substrates shall be in accordance with codified requirements to the satisfaction of the Authority Having Jurisdiction. Re-fasten any loose decking panels, and check for protruding nail heads. Sweep the substrate thoroughly to remove any dust and debris prior to application, and prime the substrate (if applicable).

### 3.3 **FBC (non-HVHZ) and FBC Residential:**

3.3.1 Refer to [Section 3.3.2](#) herein for underlayments having prescriptive codified minimum attached requirements or [Section 4.7.2](#) herein for underlayment systems having maximum design pressures established in accordance with FBC [1504.2.1.4](#).

3.3.2 Prescriptive Underlayment Systems for use in NON-TILE applications:

3.3.2.1	<b>CODE REFERENCE:</b> <a href="#">1507.1.1.1</a> or <a href="#">R905.1.1.1</a> , <b>Option 1:</b>
	<b>APPLICATION:</b> Underlayment adhered to deck
	<b>DECK DESCRIPTION:</b> Code-minimum wood deck to the satisfaction of the Authority Having Jurisdiction.
	<b>UNDERLAYMENT:</b> <b>FT Platinum HT-SA, FT Performance SA Leak Barrier, FT Platinum HT-B, or FT Premier Butyl Leak Barrier</b> self-adhered in accordance with FBC Section 1507.1.1.1(1) or R905.1.1.1(1) and back-nailed in accordance with the manufacturer's requirements.
	<b>SURFACING:</b> FBC Approved asphalt shingles, metal roof panels or metal shingles, slate or slate type shingles, subject to the allowable roof covers in <a href="#">Table 2a</a> herein.

<sup>1</sup> Agreement between purchaser and seller, as set forth in Section 4.3, Note 1 of ASTM D1970-17, should be established as to slip resistance.



# NEMO EVALUATIONS REPORT

Report No.: NER-FTS-002.B.R3  
Revision 3: 2025-06-25  
Page 3 of 7

FT Synthetics, Inc.  
FL46754-R3



3.3.2.2

**CODE REFERENCE:** [1507.1.1.1](#) or [R905.1.1.1](#), **Option 2:**  
**APPLICATION:** Self-adhering strips to deck-joints followed by underlayment mechanically attached to deck

**DECK DESCRIPTION:** Code-minimum wood deck to the satisfaction of the Authority Having Jurisdiction

**SECONDARY WATER BARRIER:** Min. 3 3/4-inch wide strips of **FT Platinum HT-SA, FT Performance SA Leak Barrier, FT Platinum HT-B, or FT Premier Butyl Leak Barrier** self-adhered over joints of the roof deck prior to installation of subsequent layer(s) in accordance with FBC Section 1507.1.1.1(2) or R905.1.1.1(2). Do not overlap end-joints or T-joints. All end-joints and T-joints shall be butted firmly side by side, flush with each other but not overlapped.

**UNDERLAYMENT:** FBC Approved, ASTM D226 Type II, ASTM D4869 Type III or IV, ASTM D6757 or ASTM D8257 underlayment in accordance with FBC Table 1507.1.1.1 or Table R905.1.1.1, with a minimum 4-inch side lap and 6-inch end lap, mechanically fastened to deck.

**FASTENERS:** Min. 0.083-inch diameter annular ring or deformed shank nails with metal or plastic caps with a nominal cap diameter of not less than 1-inch and minimum thickness as follows. Note: Metal caps are required where the ultimate design wind speed,  $V_{ult}$ , equals or exceeds 170 mph.

Cap Type	Minimum thickness
Metal cap	32 ga. sheet metal
Power-driven metal cap	0.010-inch
Plastic cap	0.035-inch (outside edge thickness)

The nail shall be of sufficient length to penetrate through the roof sheathing, or not less than 0.75-inch into the roof sheathing.

**FASTENING:** Grid pattern of 12-inches between the overlaps and 6-inch spacing at the overlaps, in accordance with FBC Table 1507.1.1.1 or Table R905.1.1.1

**SURFACING:** FBC Approved prepared roof cover, subject to the limitations in FBC Table 1507.1.1.1 or Table R905.1.1.1.

3.3.2.3

**CODE REFERENCE:** [1507.1.1.1](#) or [R905.1.1.1](#), **Option 1 combined with Option 2 or 3:**  
**APPLICATION:** Optional self-adhering strips to deck-joints followed by base sheet mechanically fastened to deck followed by underlayment adhered to base sheet

**DECK DESCRIPTION:** Code-minimum wood deck to the satisfaction of the Authority Having Jurisdiction

**SECONDARY WATER BARRIER:** (Optional) Min. 3 3/4-inch wide strips of **FT Platinum HT-SA, FT Performance SA Leak Barrier, FT Platinum HT-B, or FT Premier Butyl Leak Barrier** self-adhered over joints of the roof deck prior to installation of subsequent layer(s) in accordance with FBC Section 1507.1.1.1(2) or R905.1.1.1(2). Do not overlap end-joints or T-joints. All end-joints and T-joints shall be butted firmly side by side, flush with each other but not overlapped.

**BASE SHEET:** One (1) layer of FBC Approved, ASTM D226 Type II, ASTM D4869 Type III or IV or ASTM D8257 underlayment in accordance with FBC Table 1507.1.1.1 or Table R905.1.1.1, with a minimum 4-inch side lap and 6-inch end lap or two (2) layers of FBC Approved, ASTM D226 Type II, ASTM D4869 Type III or IV or ASTM D8257 in accordance with FBC Section 1507.1.1.1(3) or R905.1.1.1(3), mechanically fastened to deck

**FASTENERS:** Min. 0.083-inch diameter annular ring or deformed shank nails with metal or plastic caps with a nominal cap diameter of not less than 1-inch and minimum thickness as follows. Note: Metal caps are required where the ultimate design wind speed,  $V_{ult}$ , equals or exceeds 170 mph.

Cap Type	Minimum thickness
Metal cap	32 ga. sheet metal
Power-driven metal cap	0.010-inch
Plastic cap	0.035-inch (outside edge thickness)

The nail shall be of sufficient length to penetrate through the roof sheathing, or not less than 0.75-inch into the roof sheathing.

**FASTENING:** Grid pattern of 12-inches between the overlaps and 6-inch spacing at the overlaps, in accordance with FBC Table 1507.1.1.1 or Table R905.1.1.1 or FBC Section 1507.1.1.1(3) or R905.1.1.1(3).

**UNDERLAYMENT:** **FT Platinum HT-SA, FT Performance SA Leak Barrier, FT Platinum HT-B, or FT Premier Butyl Leak Barrier** self-adhered in accordance with FBC Section 1507.1.1.1(1) or R905.1.1.1(1) and back-nailed in accordance with the manufacturer's requirements.

**SURFACING:** FBC Approved asphalt shingles, metal roof panels or metal shingles, slate or slate type shingles, subject to the allowable roof covers in [Table 2a](#) herein.



# NEMO EVALUATIONS REPORT

Report No.: NER-FTS-002.B.R3  
Revision 3: 2025-06-25

FT Synthetics, Inc.

FL46754-R3



ISO/IEC 17065

PCA-145

NEMO|cert.® Page 4 of 7

## 3.4 FBC HVHZ (Broward and Miami-Dade Counties):

3.4.1 Refer to [Section 3.4.2](#) herein for underlayments having prescriptive codified minimum attachment requirements or [Section 4.7.2](#) herein for underlayment systems having maximum design pressures established in accordance with [TAS 103](#).

3.4.2 Prescriptive Underlayment Systems for use in NON-TILE applications:

### 3.4.2.1 CODE REFERENCE: [1518.2.1, Option 1:](#)

**APPLICATION:** Underlayment adhered to deck

DECK DESCRIPTION: Code-minimum wood deck to the satisfaction of the Authority Having Jurisdiction.

UNDERLAYMENT: **FT Platinum HT-SA, FT Performance SA Leak Barrier, FT Platinum HT-B, or FT Premier Butyl Leak Barrier** self-adhered in accordance with FBC Section 1518.2.1(1) and back-nailed max. 12-inch o.c. using FBC HVHZ Approved nails and tin caps (FBC HVHZ [1517.5](#)).

SURFACING: FBC HVHZ Approved asphalt shingles, metal roof panels or metal shingles, slate or slate type shingles, subject to the allowable roof covers in [Table 2a](#) herein.

### 3.4.2.2 CODE REFERENCE: [1518.2.1, Option 2:](#)

**APPLICATION:** Self-adhering strips to deck-joints followed by underlayment mechanically attached to deck

DECK DESCRIPTION: Code-minimum wood deck to the satisfaction of the Authority Having Jurisdiction

SECONDARY WATER BARRIER: Min. 3 3/4-inch wide strips of **FT Platinum HT-SA, FT Performance SA Leak Barrier, FT Platinum HT-B, or FT Premier Butyl Leak Barrier** self-adhered over joints of the roof deck prior to installation of subsequent layer(s) in accordance with FBC Section 1518.2.1(2). Do not overlap end-joints or T-joints. All end-joints and T-joints shall be butted firmly side by side, flush with each other but not overlapped.

UNDERLAYMENT: FBC HVHZ Approved, ASTM D226 Type II, ASTM D4869 Type III or IV or ASTM D8257 underlayment in accordance with FBC Table 1518.2.1, with a minimum 4-inch side lap and 6-inch end lap, mechanically fastened to deck

FASTENING: FBC HVHZ Approved nails and tin caps (FBC HVHZ [1517.5](#)), grid pattern of 12-inches between the overlaps and 6-inch spacing at the overlaps, in accordance with FBC Table 1518.2.1.

SURFACING: FBC HVHZ Approved prepared roof cover, subject to the limitations in FBC Table 1518.2.1.

### 3.4.2.3 CODE REFERENCE: [1518.2.1, Option 1 combined with Option 2 or 3:](#)

**APPLICATION:** Optional self-adhering strips to deck-joints followed by base sheet mechanically fastened to deck followed by underlayment adhered to base sheet

DECK DESCRIPTION: Code-minimum wood deck to the satisfaction of the Authority Having Jurisdiction

SECONDARY WATER BARRIER: (Optional) Min. 3 3/4-inch wide strips of **FT Platinum HT-SA, FT Performance SA Leak Barrier, FT Platinum HT-B, or FT Premier Butyl Leak Barrier** self-adhered over joints of the roof deck prior to installation of subsequent layer(s) in accordance with FBC Section 1518.2.1(2). Do not overlap end-joints or T-joints. All end-joints and T-joints shall be butted firmly side by side, flush with each other but not overlapped.

BASE SHEET: One (1) layer of FBC Approved, ASTM D226 Type II, ASTM D4869 Type III or IV or ASTM D8257 underlayment in accordance with FBC Table 1518.2.1, with a minimum 4-inch side lap and 6-inch end lap or two (2) layers of FBC Approved, ASTM D226 Type II, ASTM D4869 Type III or IV or ASTM D8257 underlayment in accordance with FBC Section 1518.2.1(3), mechanically fastened to deck

FASTENING: FBC HVHZ Approved nails and tin caps (FBC HVHZ [1517.5](#)), grid pattern of 12-inches between the overlaps and 6-inch spacing at the overlaps, in accordance with FBC Table 1518.2.1 or FBC Section 1518.2.1(3).

UNDERLAYMENT: **FT Platinum HT-SA, FT Performance SA Leak Barrier, FT Platinum HT-B, or FT Premier Butyl Leak Barrier** self-adhered in accordance with FBC Section 1518.2.1(1) and back-nailed max. 12-inch o.c. using FBC HVHZ Approved nails and tin caps (FBC HVHZ [1517.5](#)).

SURFACING: FBC HVHZ Approved asphalt shingles, metal roof panels or metal shingles, slate or slate type shingles, subject to the allowable roof covers in [Table 2a](#) herein.



# NEMO EVALUATIONS REPORT

Report No.: NER-FTS-002.B.R3  
Revision 3: 2025-06-25  
Page 5 of 7

FT Synthetics, Inc.  
FL46754-R3



## 4. LIMITATIONS OF USE:

- 4.1 This is a building code evaluation. NEMO CERT, LLC is not, in any way, the Designer of Record for any project on which this NER, or previous versions thereof, is/was used for permitting or design guidance. NERs are not to be construed as representing any attributes not specifically listed, nor are NERs to be construed as an endorsement of the subject of the report or a recommendation for its use. There is no warranty, express or implied, as to any finding or other matter in this report, or as to any product covered by the report.
- 4.2 This NER pertains to above-deck roof components. Roof decks and structural members shall be in accordance with FBC requirements to the satisfaction of the Authority Having Jurisdiction.
- 4.3 **FT Platinum HT Roof Underlayments** may be used with any prepared roof cover where the product is specifically referenced within FBC approval documents. If not listed, a request may be made to the Authority Having Jurisdiction for approval based on this NER combined with supporting data for the prepared roof covering.
- 4.4 **Fire Classification:**  
This NER does not include evaluation of fire classification. Refer to **FBC 1505 or 1516** for requirements and limitations regarding roof assembly fire classification.
- 4.5 **Allowable Roof Covers:**  
Table 2a lists allowable roof cover types, subject to fire classification referenced in Section 4.4 herein (if applicable).

UNDERLAYMENT	ROOF COVER	FBC AND FBC-R SECTION(S)		FBC HVHZ SECTIONS	
		SECTION	USE	SECTION	USE
FT Platinum HT-SA, FT Performance SA Leak Barrier	Asphalt Shingles	1507.2, R905.2	Yes	RAS 115, 1518.2.1	Yes
	Roof Tile	1507.3, R905.3	Yes <sup>2</sup>	RAS 118, 119 or 120	No
	Metal Shingles or Panels	1507.4, 1507.5, R905.4, R905.10	Yes	RAS 133, 1518.2.1	Yes
	Slate or Slate-Type Shingles	1507.7, R905.6	Yes	1518.2.1	Yes
	Wood Shingles or Shakes	1507.8, 1507.9, R905.7, R905.8	Yes <sup>3</sup>	RAS 130, 1518.10	Yes <sup>3</sup>
FT Platinum HT-B, FT Premier Butyl Leak Barrier	Asphalt Shingles	1507.2, R905.2	Yes	RAS 115, 1518.2.1	Yes
	Roof Tile	1507.3, R905.3	No	RAS 118, 119 or 120	No
	Metal Shingles or Panels	1507.4, 1507.5, R905.4, R905.10	Yes	RAS 133, 1518.2.1	Yes
	Slate or Slate-Type Shingles	1507.7, R905.6	Yes	1518.2.1	Yes
	Wood Shingles or Shakes	1507.8, 1507.9, R905.7, R905.8	Yes <sup>3</sup>	RAS 130, 1518.10	Yes <sup>3</sup>

- 4.5.1 In addition to the codified roof cover options noted above, allowable roof covers include synthetic or composite shingles, slate or shakes holding current [Florida Product Approval](#) (statewide or local).
- 4.5.2 Adhesive-set tile is limited to use of following underlayment / tile-adhesive combinations.

UNDERLAYMENT	ADHESIVE	CODE COMPLIANCE REPORT
		FBC FPA
FT Platinum HT-SA, FT Performance SA Leak Barrier	DAP "StormBond"	FL14506
	DAP "StormBond 2"	FL14506
	DuPont "Tile Bond"	FL22525
	ICP "Polysset AH-160	FL6332

\*Refer to Tile Manufacturer's or Adhesive Manufacturer's compliance documentation for Overturning Moment Resistance Performance

<sup>2</sup> For roof tile, used with mechanically fastened tile or adhesive-set tile using adhesive options set forth in [Table 2b](#).

<sup>3</sup> For wood shakes and wood shingles, limited to use as joint-strips per FBC 1507.1.1.1(2), 1518.2.1(2) or R905.1.1.1(2) or as cap sheet atop mechanically attached, FBC Approved ASTM D226 Type II or ASTM D4869 Type III or IV base sheet.



# NEMO EVALUATIONS REPORT

Report No.: NER-FTS-002.B.R3  
 Revision 3: 2025-06-25  
 Page 6 of 7

FT Synthetics, Inc.  
 FL46754-R3



## 4.6 Allowable Substrates:

TABLE 3: SUBSTRATE OPTIONS FOR ADHERED UNDERLAYMENTS				
UNDERLAYMENT	APPLICATION	SUBSTRATES (DESIGNED TO MEET WIND LOADS FOR PROJECT)		
		TYPE	PRIMER	MATERIAL(S)
FT Platinum HT-SA, FT Performance SA Leak Barrier	self-adhering	Deck / sheathing	(Optional) ASTM D41	Plywood or OSB
		Base Sheet	None	ASTM D226, Type II felt
FT Platinum HT-B, FT Premier Butyl Leak Barrier	self-adhering	Deck / sheathing	None	Plywood

## 4.7 Attachment Limitations:

4.7.1 For use in NON-TILE applications under the FBC and FBC Residential, refer to [Section 3](#) herein and the applicable Code requirements.

## 4.7.2 Wind Resistance for Underlayment Systems in Tile Roof Applications under the FBC and FBC Residential:

The following wind uplift limitations apply to tile underlayment systems per FBC 1504.2.1.4 and Section 7 of TAS 103. The Maximum Design Pressure ('MDP') is the result of testing for wind load resistance based on allowable wind loads, and reflects the ultimate passing pressure divided by 2 (the 2 to 1 margin of safety has already been applied).

TABLE 4A: ALLOWABLE DESIGN PRESSURES, ADHERED, DIRECT-TO-DECK UNDERLAYMENT SYSTEMS				
*Nails shall be corrosion resistant and be of sufficient length to penetrate through the sheathing by min. 3/16-inch				
SYSTEM No.	DECK	PRIMER	UNDERLAYMENT	MAX. DESIGN PRESSURE (PSF)
1	Plywood, APA rated sheathing, 40/20, Exposure 1, PS1, 19/32 category	(Optional) ASTM D41	FT Platinum HT-SA or FT Performance SA Leak Barrier, self-adhered and back-nailed in accordance with FT Synthetics installation instructions, max. 12-inch o.c.	-97.5
2	Plywood, APA rated sheathing, 32/16, Exposure 1, PS1, 15/32 category	None	FT Platinum HT-SA or FT Performance SA Leak Barrier, self-adhered and back-nailed using 12 ga. x 3/8-inch head diameter annular ring shank roofing nails* and 32 ga. x 1-5/8-inch diameter tin caps, max. 12-inch o.c.	-105.0

## 4.8 Exposure Limitations:

TABLE 5: EXPOSURE LIMITATIONS		
UNDERLAYMENT	PREPARED ROOF COVER INSTALLATION TYPE (OVERTOP OF UNDERLAYMENT)	MAXIMUM EXPOSURE (DAYS)
FT Platinum HT-SA, FT Performance SA Leak Barrier	Mechanically attached or adhesive-set tile roof system	180
FT Platinum HT-B, FT Premier Butyl Leak Barrier	Mechanically attached	180



# NEMO EVALUATIONS REPORT

Report No.: NER-FTS-002.B.R3  
Revision 3: 2025-06-25  
Page 7 of 7

FT Synthetics, Inc.  
FL46754-R3



## 4.9 Tile Slippage Limitations:

When loading roof tiles on the underlayment, the maximum roof slope shall be as follows. Slopes in excess of these limitations require the use of battens or loading boards during loading of the roof tiles.

TABLE 6: TILE SLIPPAGE LIMITATIONS (NON-HVHZ ONLY)			
UNDERLAYMENT	TILE PROFILE	STAGING METHOD	MAXIMUM SLOPE
FT Platinum HT-SA, FT Performance SA Leak Barrier	Flat	10-tile stack	4:12
	Lugged	10-tile stack	4:12

4.10 All components in the roof assembly shall have quality assurance audit in accordance with F.A.C. [Rule 61G20-3](#). Refer to the Product Approval of the component manufacturer for components mentioned herein that are produced by a Product Manufacturer other than this report holder.

- END OF NER -